

## Belt Sander Table User Manual



### 1. Product description

The 75 mm x 190 mm table is designed for use with belt sanders. It allows you to adjust the angle of the table plane in relation to the sander belt, which allows for precise sanding of various materials.

The table fits the following models:

- 50x2000
- 75x2000

### 2. Material and maintenance

- **Material:** The table is made of steel, covered with a galvanic coating, which makes it resistant to corrosion.
- **Maintenance:** To prevent the table top from rusting, it should be regularly maintained. It is recommended to:
  - Clean the top after each use from material residue and dust.
  - Apply protective oil or anti-corrosion agent at least once a month to maintain proper surface protection.

### 3. Table assembly

1. Preparation: Make sure you have all the necessary tools and assembly elements.

#### 2. Assembly:

- Attach the table to the appropriate location on the belt sander using the provided screws and nuts.

- Make sure the table is stable and free from play.

### **3. Adjusting the angle:**

- Use the M8 screw to set the desired angle of the table plane to the sander belt.
- Lock the setting to prevent accidental movement.

### **4. Use**

- Before starting work, make sure that all components are properly assembled and locked.
- Always wear appropriate personal protective equipment such as safety glasses and gloves when sanding.
- Do not exceed the maximum material thickness that can be sanded on the table.

### **5. Safety**

- Do not use the table if you notice any damage.
- Regularly check the condition of the table and its attachment to the sander.
- Always switch off the sander before making any adjustments or maintenance.

### **6. Storage**

- After use, clean the table and store it in a dry place to minimize the risk of rust.

### **7. Service and support**

If you have any problems with the assembly or use of the table, contact the manufacturer or an authorized service center.

Remember that proper use and maintenance of the table will ensure its longevity and safety during operation.